


FLEXADUX® P 2 V 10

Light weight and very flexible PVC ducting





Material:
PVC

Colour:
white

Single Length:
6, 10 and 15 m

Temperature Resistance:
0° up to + 70° C

Applications:
Suction of kitchen fumes or warm air of tumble dryers and solariums, air-conditioning and ventilation

Properties:
Excellent flexibility, good compressibility

Stand:
23.10.2019

TECHNICAL DATA

Dia. (mm)	Weight (kg/m)	Material Thickness (mm)	Bending radius (mm)	Max. Work. Press. (bar)	Max. Vacuum (bar)
25	0,13	0,4	18	0,45	0,22
30	0,17	0,4	21	0,40	0,20
40	0,19	0,4	28	0,40	0,18
50	0,24	0,4	35	0,35	0,15
60	0,29	0,4	42	0,35	0,14
70	0,34	0,4	49	0,30	0,12
75	0,36	0,4	53	0,30	0,10
80	0,39	0,4	56	0,25	0,09
100	0,50	0,4	70	0,20	0,08
120	0,60	0,4	85	0,20	0,07
125	0,62	0,4	88	0,15	0,06
140	0,70	0,4	95	0,10	0,06
150	0,73	0,4	105	0,08	0,05
175	0,81	0,4	123	0,06	0,04
200	0,99	0,4	140	0,05	0,03
250	1,23	0,4	175	0,04	0,03
300	1,49	0,4	210	0,03	0,02
350	1,98	0,4	245	0,02	0,02
400	2,26	0,4	280	0,02	0,01
450	2,54	0,4	315	0,01	0,01
500	2,83	0,4	350	0,01	0,01
600	4,60	0,4	400	0,01	0,01
710	5,44	0,4	475	0,01	0,01
800	6,13	0,4	535	0,01	0,01

Further diameters available upon request!
Technical data are based on + 23° C.

SCHAUENBURG RUHRKUNSTSTOFF GMBH
Weseler Str. 35 · 45478 Mülheim-Ruhr · Germany · Tel. +49 (0) 2 08 99 91- 0 · Fax +49 (0) 2 08 5 33 74 · mail@schauenburg-rk.com