


FLEXADUX® P 7 M Street

Heavy-duty and flexible Polyurethane ducting





Material:
Polyether-Polyurethane

Colour:
Clear with black cover

Single Length:
10 and 15 m

Temperature Resistance:
- 40° up to + 100° C

Applications:
Suction and discharging of abrasive materials

Quality:
Resistant to hydrolysis and microbes, non toxic, smooth bore - additional improved flow channel by outer folding, good flexibility, excellent abrasion resistance, resistant to oil and petrols, free of halogen and softeners

Stand:
23.10.2019

TECHNICAL DATA

Dia. (mm)	Weight (kg/m)	Material Thickness (mm)	Bending radius (mm)	Max. Work.Press. (bar)	Max. Vacuum (bar)
180	2,30	1,4	220	0,30	0,20
190	2,45	1,4	230	0,30	0,20
200	2,60	1,4	240	0,30	0,20
300	3,80	1,4	360	0,20	0,20

Further diameters available upon request!
Technical data are based on + 23° C.

SCHAUENBURG RUHRKUNSTSTOFF GMBH
Weseler Str. 35 · 45478 Mülheim-Ruhr · Germany · Tel. +49 (0) 2 08 99 91- 0 · Fax +49 (0) 2 08 5 33 74 · mail@schauenburg-rk.com