



FLEXADUX® P 2 SP-TPR

Light weight and very flexible TPE ducting





Material:
TPE

Single Length:
6, 10 and 15 m

Temperature Resistance:
- 40° bis + 135° C (short-term 150° C)

Applications:
Suction of air, fumes and gases, ventilation, air-conditioning in vehicle construction.

Properties:
Good temperature resistance, free of halogens and softeners, good chemical resistance, excellent flexibility, good UV-resistence

Stand:
08.02.2022

TECHNICAL DATA

Dia. (mm)	Weight (kg/m)	Material Thickness (mm)	Bending radius (mm)	Max. Work. Press. (bar)	Max. Vacuum (bar)
40	0,19	0,4	28	0,34	0,15
50	0,24	0,4	35	0,27	0,12
60	0,29	0,4	42	0,22	0,10
70	0,34	0,4	49	0,20	0,08
75	0,36	0,4	50	0,18	0,08
80	0,39	0,4	56	0,17	0,07
100	0,50	0,4	70	0,14	0,06
120	0,60	0,4	85	0,12	0,06
125	0,62	0,4	88	0,11	0,05
140	0,70	0,4	95	0,10	0,05
150	0,73	0,4	105	0,08	0,04
175	0,81	0,4	123	0,06	0,03
200	0,99	0,4	140	0,05	0,03
250	1,23	0,4	175	0,04	0,02
300	1,49	0,4	210	0,03	0,02
350	2,01	0,4	250	0,02	0,01
400	2,29	0,4	285	0,02	0,01
450	2,58	0,4	320	0,01	0,01
500	2,86	0,4	355	0,01	0,01

Further diameters available upon request!
Technical data are based on + 23° C.

SCHAUENBURG RUHRKUNSTSTOFF GMBH
Weseler Str. 35 · 45478 Mülheim-Ruhr · Germany · Tel. +49 (0) 2 08 99 91- 0 · Fax +49 (0) 2 08 5 33 74 · mail@schauenburg-rk.com