



FLEXADUX® P 7 M PU AE

Heavy weight and flexible Polyurethane ducting





Material:
Polyether-polyurethan, clear

Single Length:
10 and 15 m

Temperature Resistance:
- 40° up to + 100° C

Applications:
Suction and discharging of abrasive materials

Properties:
Resistant to hydrolysis and microbes, non toxic, very smooth bore, good flexibility, excellent abrasion resistance, resistant to oil and petrols, free of halogen and softeners

Stand:
02.07.2020

TECHNICAL DATA

Dia. (mm)	Weight (kg/m)	Wall-Thickness (mm)	Bend. Rad. (mm)	max. Work.Press. (bar)	max. Vacuum (bar)
25	0,34	1,40	38	3,00	0,90
30	0,42	1,40	45	3,00	0,90
40	0,54	1,40	60	2,30	0,70
50	0,67	1,40	75	1,90	0,60
60	0,80	1,40	90	1,80	0,55
70	0,92	1,40	105	1,60	0,50
75	0,99	1,40	113	1,40	0,50
80	1,05	1,40	120	1,20	0,45
90	1,18	1,40	135	1,10	0,40
100	1,52	1,40	150	1,10	0,40
110	1,67	1,40	165	1,00	0,35
120	1,82	1,40	180	0,90	0,30
125	1,89	1,40	188	0,80	0,25
140	2,11	1,40	210	0,70	0,20
150	2,43	1,40	225	0,70	0,20
160	2,59	1,40	240	0,60	0,20
175	2,82	1,40	263	0,55	0,15
200	3,37	1,40	300	0,50	0,15
225	3,78	1,40	338	0,40	0,10
250	4,19	1,40	375	0,30	0,10
300	5,01	1,40	450	0,30	0,10
350	5,33	1,40	525	0,25	0,09
400	6,08	1,40	600	0,20	0,09
450	6,83	1,40	675	0,10	0,08

Further diameters available upon request!
Technical data are based on + 23° C.

SCHAUENBURG RUHRKUNSTSTOFF GMBH
Weseler Str. 35 · 45478 Mülheim-Ruhr · Germany · Tel. +49 (0) 2 08 99 91- 0 · Fax +49 (0) 2 08 5 33 74 · mail@schauenburg-rk.com